


TPC Series

Low ESR TACmicrochip®



- Low ESR TACmicrochip® capacitor
- Smallest and low profile tantalum
- CV range: 1.0-100µF / 3-25V
- 4 case sizes available
- Power supply applications



CASE DIMENSIONS: millimeters (inches)

Code	EIA Code	EIA Metric	Length (L)	Width (W)	Height (H)	Termination Spacing(S)	Minimum Termination Length (Lt)	Average Mass
H	0805	2012-10	2.00 ^{+0.20} _{-0.00} (0.079 ^{+0.008} _{-0.000})	1.35 ^{+0.15} _{-0.00} (0.053 ^{+0.006} _{-0.000})	1.00 max.	0.70 min	0.15 min.	17.1mg
K	0402	1005-07	1.00 ^{+0.20} _{-0.00} (0.039 ^{+0.008} _{-0.000})	0.50 ^{+0.20} _{-0.00} (0.020 ^{+0.008} _{-0.000})	0.50 ^{+0.20} _{-0.00} (0.020 ^{+0.008} _{-0.000})	0.40 min	0.10 (0.004)	2.8mg
L	0603	1608-10	1.60 ^{+0.20} _{-0.00} (0.063 ^{+0.008} _{-0.000})	0.85 ^{+0.15} _{-0.00} (0.033 ^{+0.006} _{-0.000})	0.85 ^{+0.15} _{-0.00} (0.033 ^{+0.006} _{-0.000})	0.55 min	0.15 (0.006)	8.6mg
R	0805	2012-15	2.00 ^{+0.20} _{-0.00} (0.079 ^{+0.008} _{-0.000})	1.35 ^{+0.15} _{-0.00} (0.053 ^{+0.006} _{-0.000})	1.35 ^{+0.15} _{-0.00} (0.053 ^{+0.006} _{-0.000})	0.70 min	0.15 (0.006)	29.9mg

HOW TO ORDER

TPC

Type
TACmicrochip®

R

Case Size
See table
above

106

Capacitance Code
pF code: 1st two digits
represent significant figures,
3rd digit represents multiplier
(number of zeros to follow)

M

Tolerance
K=±10%
M=±20%

010

Rated DC Voltage
003=3Vdc
004=4Vdc
006=6.3Vdc
010=10Vdc
016=16Vdc
020=20Vdc
025=25Vdc

R

Packaging
R, P = 7" Standard Tin
Termination Plastic Tape
X, Q = 4 $\frac{1}{4}$ " Standard Tin
Termination Plastic Tape
A, M = 7" Gold Termination
Plastic Tape
F, N = 4 $\frac{1}{4}$ " Gold Termination
Plastic Tape

1800

ESR in mΩ

TECHNICAL SPECIFICATIONS

Technical Data:

All technical data relate to an ambient temperature of +25°C

Capacitance Range:

1.0 µF to 100 µF

Capacitance Tolerance:

±10%; ±20%

Leakage Current DCL:

0.01CV or 0.5µA whichever is the greater

Rated Voltage (V_R)

≤ +85°C: 3 4 6.3 10 16 20 25

Category Voltage (V_C)

≤ +125°C: 2 2.7 4 7 10 13 17

Surge Voltage (V_S)

≤ +85°C: 3.9 5.2 8 13 20 26 32

Surge Voltage (V_S)

≤ +125°C: 2.6 3.2 5 8 12 16 20

Temperature Range:

-55°C to +125°C

Reliability:

1% per 1000 hours at 85°C, V_R with 0.1Ω/V series impedance,
60% confidence level

Termination Finish:

Nickel and Tin Plating (standard),
Nickel and Gold Plating option available upon request

TPC Series



Low ESR TACmicrochip®

LOW ESR RANGE (LETTER DENOTES CASE SIZE)

Capacitance		Voltage Rating DC (V _R) at 85°C						
µF	Code	3.0V	4.0V	6.3V	10V	16V	20V	25V
1.0	105				L(5000)			R(3000)
1.5	155							
2.2	225			K(8000)/L(5000)	L(5000)	L(5000)		
3.3	335				L(5000)			
4.7	475	K(8000)			L(5000) ^M		R(1500) ^{M*}	
6.8	685							
10	106			L(4000) ^M	H(2500) L(4000) ^M ,R(1800)	R(1800)		
15	156			R(1800)	R(1500)			
22	226		L(5000) ^M /R(1800)	R(1500)	R(1500)			
33	336	R(1800)	H(1500) ^M /R(1500)		R(1500) ^M			
47	476	R(1500)		R(1800) ^M				
68	686							
100	107		R(1000) ^M					

Codes shown are examples of ESR values offered on certain CV and case size.
Other codes and ESR values available upon request.

Released codes (M tolerance only)

*Code under development – subject to change

Note: Voltage ratings are minimum values. AVX reserves the right to supply higher ratings in the same case size, to the same reliability standards





TPC Series

Low ESR TACmicrochip®

RATINGS & PART NUMBER REFERENCE

AVX Part No.	EIA	Case Size	Cap (μF)	Rated Voltage (V)	DCL (μA) Max.	DF % Max.	ESR Max. ($\text{m}\Omega$) @100kHz	MSL	100kHz Ripple Current Ratings (A)			100kHz Ripple Voltage Ratings (V)		
									25°C	85°C	125°C	25°C	85°C	125°C
3 Volt @ 85°C (2 Volt @ 125°C)														
TPCK475*003#8000	0402	K	4.7	3	0.5	12	8000	1	0.043	0.039	0.017	0.346	0.312	0.139
TPCR336*003#1800	0805	R	33	3	1.0	10	1800	1	0.158	0.142	0.063	0.285	0.256	0.114
TPCR476*003#1500	0805	R	47	3	1.5	10	1500	1	0.173	0.156	0.069	0.260	0.234	0.104
4 Volt @ 85°C (2.7 Volt @ 125°C)														
TPCL226M004#5000	0603	L	22	4	0.9	6	5000	1	0.071	0.064	0.028	0.354	0.318	0.141
TPCR226*004#1800	0805	R	22	4	0.9	8	1800	1	0.158	0.142	0.063	0.285	0.256	0.114
TPCH336M004#1500	0805	H	33	4	1.3	14	1500	1	0.163	0.147	0.065	0.245	0.221	0.098
TPCR336*004#1500	0805	R	33	4	1.3	10	1500	1	0.173	0.156	0.069	0.260	0.234	0.104
TPCR107M004#1000	0805	R	100	4	4.0	30	1000	1	0.212	0.191	0.085	0.212	0.191	0.085
6.3 Volt @ 85°C (4 Volt @ 125°C)														
TPCK225*006#8000	0402	K	2.2	6.3	0.5	8	8000	1	0.043	0.039	0.017	0.346	0.312	0.139
TPCL225*006#5000	0603	L	2.2	6.3	0.5	6	5000	1	0.071	0.064	0.028	0.354	0.318	0.141
TPCL106M006#4000	0603	L	10	6.3	0.6	10	4000	1	0.079	0.071	0.032	0.316	0.285	0.126
TPCR156*006#1800	0805	R	15	6.3	0.9	8	1800	1	0.158	0.142	0.063	0.285	0.256	0.114
TPCR226*006#1500	0805	R	22	6.3	1.4	10	1500	1	0.173	0.156	0.069	0.260	0.234	0.104
TPCR476M006#1800	0805	R	47	6.3	3.0	20	1800	1	0.158	0.142	0.063	0.285	0.256	0.114
10 Volt @ 85°C (7 Volt @ 125°C)														
TPCL105*010#5000	0603	L	1.0	10	0.5	6	5000	1	0.071	0.064	0.028	0.354	0.318	0.141
TPCL225*010#5000	0603	L	2.2	10	0.5	6	5000	1	0.071	0.064	0.028	0.354	0.318	0.141
TPCL335*010#5000	0603	L	3.3	10	0.5	8	5000	1	0.071	0.064	0.028	0.354	0.318	0.141
TPCL475M010#5000	0603	L	4.7	10	0.5	10	5000	1	0.071	0.064	0.028	0.354	0.318	0.141
TPCH106*010#2500	0805	H	10	10	1.0	8	2500	1	0.126	0.113	0.050	0.100	0.09	0.040
TPCL106M010#4000	0603	L	10	10	1.0	20	4000	1	0.079	0.071	0.032	0.316	0.285	0.126
TPCR106*010#1800	0805	R	10	10	1.0	8	1800	1	0.158	0.142	0.063	0.285	0.256	0.114
TPCR156*010#1500	0805	R	15	10	1.5	10	1500	1	0.173	0.156	0.069	0.260	0.234	0.104
TPCR226*010#1500	0805	R	22	10	2.2	14	1500	1	0.173	0.156	0.069	0.260	0.234	0.104
TPCR336M010#1500	0805	R	33	10	3.3	20	1500	1	0.173	0.156	0.069	0.260	0.234	0.104
16 Volt @ 85°C (10 Volt @ 125°C)														
TPCL225*016#5000	0603	L	2.2	16	0.5	10	5000	1	0.071	0.064	0.028	0.354	0.318	0.141
TPCR106*016#1800	0805	R	10	16	1.6	10	1800	1	0.158	0.142	0.063	0.285	0.256	0.114
20 Volt @ 85°C (13 Volt @ 125°C)														
TPCR475M020#1500	0805	R	4.7	20	0.9	8	1500	1	0.173	0.156	0.069	0.260	0.234	0.104
25 Volt @ 85°C (17 Volt @ 125°C)														
TPCR105*025#3000	0805	R	1.0	25	0.5	8	3000	1	0.122	0.110	0.049	0.367	0.331	0.147

Moisture Sensitivity Level (MSL) is defined according to J-STD-020.

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts.

DCL is measured at rated voltage after 5 minutes.

The EIA & CECC standards for low ESR Solid Tantalum Capacitors allow an ESR movement to 1.25 times catalogue limit post mounting.

For typical weight and composition see page 125.

NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.